



DHIYOHOUSE

HOUSE OF COAL & CONVEYOR BELTS

DHIYOHOUSE

CASA DEL CARBÓN Y CINTAS TRANSPORTADORAS



**DHIYHOUSE INC. PRIDES ITSELF IN
MANUFACTURING & SUPPLYING THE
HIGHEST QUALITY BELTS FOR THE PAST
15 YEARS.**

We work closely alongside government regulations and standards to ensure our surface and MSHA approved belts exceed market expectations and safety regulations.

For over a decade, Dhiyohouse has specialized in producing & distributing general purpose, heat & fire resistant, oil resistant, chevron, steep angle, straight warp, and other variants of conveyor belts per our client's needs.



BELT SPECIFICATIONS

Dhiyohouse specializes in the manufacturing of MSHA PART 14, and surface conveyor belting for various industrial needs



NYLON AND POLYESTER NYLON BELTING

DHIYO HOUSE RANGE OF NYLON-NYLON & POLYESTER NYLON BELTING

Belt width	8" to 84"
No. of plies	1 to 8
Edges	Cut edge & Sealed edge
Type of breaker	Nylon, Polyester
Length	Standard roll length is 1,000 FT
	The restriction on length over and above 1000 FT is subject to transportable roll diameter and weight.
Belt thickness	0.11" to 1.57"
Standards followed	MSHA & CAN-CSA

FIRE RETARDANT BELTING

SPECIFICATIONS

Surface resistance	$\leq 3 \times 10^8 \Omega$
Drum friction	Drum Temperature shall not exceed 325°C, belt shall show no sign of flame, sparks or glow
Burner flame test	With rubber cover: average ≤ 3 seconds, individual ≤ 10 seconds
	Without rubber cover: average \leq seconds, individual ≤ 15 seconds
Fabric full thickness tensile strength (KN/m)	200~4000
Work elongation	$\leq 2\%$
Elongation at break	450%
Adhesion	$\leq 5N/mm$
Rubber thickness (mm)	Top 1.5 ~ 12
	Bottom 0 ~ 4.5

HEAT RESISTANT BELTS

SPECIAL SPECIFICATIONS

Dhiyohouse provides different types of conveyor belting products suited for applications that require Heat-Resistance and Oil-Resistance



PRODUCT FEATURES

Standard widths	300mm to 2200mm (up to 5000mm, with longitudinal joint)
Ply's available	EP / NN / PP
Standard belt rating	200 to 3200 KN/M
Number of ply's	1 ply belts to 8 ply belts
Rubber cover thickness	1mm to 20mm
Color	Black
Edge	Cut edge / Molded edge
Splicing method	Hot / Cold / Mechanical
Belt identification	A unique PAN (Product Authentication Number) at every 10 meters

OIL RESISTANT BELTS

SPECIAL SPECIFICATIONS

Dhiyohouse provides different types of conveyor belting products suited for applications that require Heat-Resistance and Oil-Resistance



PRODUCT FEATURES

Standard widths	300mm to 220mm (up to 5000mm, with longitudinal joint)
Ply's available	EP / NN / PP
Standard belt rating	200 to 2500 KN/M
Number of ply's	1 ply belts to 8 ply belts
Rubber cover thickness	1mm to 20mm
Color	Black
Edge	Cut edge / Molded edge
Splicing method	Hot / Mechanical
Belt identification	A unique PAN (Product Authentication Number) at every 10 meters

**QUALITY AND DURABILITY IS HOUSED
HERE**

Through rigorous tests and constant changes, we prioritize the quality of our belts.

We believe strongly in reducing operating costs and increasing productivity for our end-users, along with continually seeking improvements in our curating and production process.



CONTACT US



798 PARK AVENUE NW, SUITE 214 NORTON, VA

PH: +1 (276) 807-4286

CELL: +1 (770) 403-0370

WEB: WWW.DHIYHOUSE.COM

EMAIL: SALES@DHIYHOUSE.COM

